PTFE Chemical Hose





Application

Suitable for various Acids & Alkaline

Standard: - EN 13765 TYPE 2

Construction: Hose made from Polypropylene fabric and films with PVC coated fabric cover, Inner & outer SS 316 wire and lined

with layer of PTFE Film. Finishing: Wrapped Surface

Temperature Range Continuous: -30°C to +140°C

Color:Red with white strip

Nominal Bore	Hose O.D. (Nom.)	Working	Pressure	Min. Bend Radius mm
mm	mm	psi	bar	
25	38	150	10	90
38	52	150	10	120
50	64	150	10	150
65	80	150	10	180
75	92	150	10	210
100	120	150	10	340
150	200	200	14	550
200	240	200	14	750
	80re mm 25 38 50 65 75 100	Bore (Nom.) mm mm 25 38 38 52 50 64 65 80 75 92 100 120 150 200	Bore (Nom.) Working mm mm psi 25 38 150 38 52 150 50 64 150 65 80 150 75 92 150 100 120 150 150 200 200	Bore (Nom.) Working Pressure mm mm psi bar 25 38 150 10 38 52 150 10 50 64 150 10 65 80 150 10 75 92 150 10 100 120 150 10 150 200 200 14

For more details or product related enquires feel free mail us: info@italflexitaly.it

Copyright © ITALFLEX Italy. - All rights reserved. Text and images are property of ITALFELX Italy is forbidden even partial reproduction of the catalogue. In the constant search for technical and functional improvements, ITALFLEX Italy reserves the right to make changes to its products without notice.