

Air Hoses



Application

For general purpose and wide range of service in general industries, Civil Engineering, Mining, Shipbuilding, Steel production, quarrying and Automobile shop, Not suited for solution containing aromatic hydrocarbon

Type: Mandrel-Built Hose

Tube: SBR / NR Compound

Finishing: Wrapped Surface

Temperature Range: -35°C to +90°C (-30°F to 195°F)

Cover : SBR Compound, Colour : Black or Yellow colour choices, Surface : Smooth or Corrugated

Technical Specifications

Part No	ID x OD		Max. Work Pressure	Burst Pressure	Standard Length	Weight
	Inch	mm	Psi	Psi		
IF631-04	1/4	6.4 x 13	300	900	100	0.15
IF631-05	5/16	8.0 x 15	300	900	100	0.22
IF631-06	3/8	9.6 x 16.5	300	900	100	0.26
IF631-08	1/2	12.7 x 22	300	900	100	0.39
IF631-10	5/8	15.9 x 26	300	900	100	0.43
IF631-12	3/4	19.0 x 28	300	900	100	0.58
IF631-16	1	25.4 x 35	300	900	100	0.80
IF631-20	1 1/4	32 x 46	300	900	100	1.00
IF631-24	1 1/2	38 x 42	300	900	40	1.40
IF631-32	2	51 x 65	300	900	40	2.10
IF631-40	2 1/2	63 x 79	300	900	40	2.45
IF631-48	3	76 x 92	300	900	40	3.40
IF631-64	4	102 x 120	300	900	40	4.45

For more details or product related enquires feel free mail us: info@italflexitaly.it