

# Tank Truck Hose



## Application

The industry standard for tank truck, in-plant operations to transfer oil and other petroleum base products up to 50% aromatic content.

**Core:** Nitrile Synthetic Rubber Blended Reinforcement: Spiral-plied synthetic fabric with helix wire

**Temperature Range Continuous:** -20°C to + 85°C

**Cover:** Black abrasion, oil, weather & ozone resistant Neoprene rubber (Smooth cover)

Italflex Part No	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst	
	In	mm	In	mm	psi	bar	psi	bar
IF615-32	2	50.7	2.68	68.6	580	40	1740	120
IF615-48	3	76.3	3.9	99.1	580	40	1740	120
IF615-64	4	101.8	5.1	128.6	580	40	1740	120
IF615-96	6	152.2	6.8	173.2	580	40	1740	120

For more details or product related enquires feel free mail us: [info@italflexitaly.it](mailto:info@italflexitaly.it)

Copyright © ITALFLEX Italy. - All rights reserved. Text and images are property of ITALFLEX Italy is forbidden even partial reproduction of the catalogue. In the constant search for technical and functional improvements, ITALFLEX Italy reserves the right to make changes to its products without notice.