

Bulk / Cement Suction & Discharge Hoses

Part No. IF 628



Application

Abrasion resistant tube and cover fabricated with highest quality elastomer compounds for maximum performance. Used in the transfer of dry materials & slurries and ideal for dry cement, pebble, lime brine, barite and other abrasive media.

Type: Mandrel-Built Hose

Finishing: Wrapped Surface

Cover :Black abrasion, weather & ozone Resistant synthetic rubber

Tube:Black abrasion NR/SBR rubber

Reinforcement:Spiral – plied synthetic fabric with helix wire.

Temperature Range:-35°C to 100°C (30°F to 212°F)

Technical Specifications

Part No	ID x OD	ID x OD	Work Pressure	Burst Pressure	Standard Length	Weight (Approx)	Bend Radius (Approx)
	Inch	MM	PSI	PSI	M	KG / M	MM
IF623-32	2.00 x 2.89	50.8 x 73.6	300	900	60	2.94	300
IF623-40	2.50 x 3.39	63.1 x 86.3	300	900	60	3.54	400
IF623-48	3.00 x 3.90	76.2 x 99.1	300	900	60	4.11	500
IF623-64	4.00 x 4.96	101.6 x 126.2	300	900	60	6.21	700
IF623-80	5.00 x 6.04	127 x 153.5	300	900	30	8.35	1000
IF623-96	6.00 x 7.20	152.4 x 183.1	300	900	30	11.18	1500
IF623-128	8.00 x 9.29	203.0 x 236.9	300	900	12	16.31	1600
IF623-160	10.00 x 11.77	254.0 x 299.3	150	450	12	29.81	2000
IF623-192	12.00 x 13.92	305.1 x 353.8	150	450	12	40.18	2750

For more details or product related enquires feel free mail us: info@italflexitaly.it